

Data Frames

An Aside About Data Sets

- Data sets are typically messy.
 - NA's might be `-9` (numeric), `"-9. Refused"`, `"-8. Don't know"`, `"-2. Missing, other not codeable to 1-5"`, or some combination of these.
 - `"Strong Democrat"` is a `1`.
 - `"Other"` is `"5. Other party {SPECIFY}"`
 - Data sets are not "tidy" (rows are observations; columns are variables).
 - Factors are strangely ordered or are character vectors.
 - Data are stored in different data files.
 - Lots of unnecessary columns or rows.
 - Uniformatively named columns, such as `var1003b`.
- The data I give you are clean and tidy.
- The skill of taking messy data files and cleaning and tidying is called "data wrangling." We talk very little about data wrangling.

Terminology

- **data set:** a collection of information stored somehow, somewhere.
- **data file:** a specific file containing a data set.
- **file type:** the specific format in which the data are stored (e.g., .xlsx, .dta, .rds, .csv)
- **data frame:** a type of object in R; think of as a “box of vectors.”
 - other objects include scalars, vectors, and functions
 - all vectors in a box have the same length (number of elements)
 - most functions for modeling and graphing are designed to work with data frames via a `data =` argument, not vectors

Data reading functions create data frames from data files.

```
read_csv(), read_dta(), read_excel(), read_rds()
```

**thinking about
data frames**

```
x <- c(6, 4, 5, 6, 2, 3) # create a numeric vector
```

x

x

```
my_logic <- c(TRUE, FALSE, FALSE) # create logical vector
```

x

my_logic

x

my_logic

```
ch.vec <- c("word1", "word2") # create character vector
```

ch.vec

x

my_logic

ch.vec

x

my_logic


```
data1 <- read_csv("nominate.csv") # read data set
```

ch.vec

x

my_logic

data1




ch.vec

x

my_logic

data1

```
> glimpse(data1)
Observations: 6,159
Variables: 6
$ congress      <int> 100, 100, 100, 100, 100, 100, 1...
$ state         <fctr> ALABAMA, ALABAMA, ALABAMA, ALA...
$ congressional_district <int> 1, 2, 3, 4, 5, 6, 7, 1, 1, 2, 3...
$ party         <fctr> Republican, Republican, Democr...
$ name          <fctr> CALLAHAN, DICKINSON, NICHOLS  ...
$ ideology_score <dbl> 0.358, 0.349, -0.039, -0.203, -...
```



ch.vec

x

my_logic

data1

congress

name

state

ideology_score

party

congressional_district

ch.vec

x

my_logic

data1

congress

name

state

ideology_score

party

congressional_district


```
submit_times <- read_rds("submit_times.rds") # read data
```

ch.vec

x

my_logic

submit_times



data1

| | |
|------------------------|-------|
| congress | name |
| state | |
| ideology_score | party |
| congressional_district | |




ch.vec


x

my_logic

submit_times



data1




ch.vec


x

my_logic

submit_times



data1



mean(x) # find the average

ch.vec

x

my_logic

submit_times

submit_time

hours_early

data1

congress

name

state

ideology_score

party

congressional_district

```
> mean(x) # find the average  
[1] 4.333333
```

ch.vec

x

my_logic

submit_times

submit_time

hours_early

data1

congress

name

state

ideology_score

party

congressional_district


```
> mean(x) # find the average  
[1] 4.333333
```

ch.vec


x

my_logic

submit_times



data1



mean(ideology_score) # find the average

ch.vec

x

my_logic

submit_times

submit_time

hours_early

data1

congress

name

state

ideology_score

party

congressional_district

```
> mean(ideology_score) # find the average
Error in mean(ideology_score) : object 'ideology_score' not
found
```

ch.vec

x

my_logic

submit_times

submit_time

hours_early

data1

congress

name

state

ideology_score

party

congressional_district

```
> mean(ideology_score) # find the average
Error in mean(ideology_score) : object 'ideology_score' not
found
```

ch.vec

x

my_logic

submit_times

submit_time

hours_early

data1

congress

name


state

ideology_score

party

congressional_district

```
> mean(ideology_score) # find the average
Error in mean(ideology_score) : object 'ideology_score' not
found
```




When looking for a vector,
R does not look inside data
frames unless you ask it.

ch.vec


x

my_logic

submit_times



data1




mean(data1\$ideology_score) # find the average

ch.vec


x

my_logic

submit_times



data1




```
> mean(data1$ideology_score)
[1] 0.08695941
```

ch.vec


x

my_logic

submit_times



data1



```
> mean(data1$ideology_score)
[1] 0.08695941
```

the key syntax

`data$variable`

However, **most** functions for modeling and graphing are designed to work with data frames via a `data =` argument, not vectors

- no: `mean()`, `sd()`, `log()`, `sqrt()`
- yes: `ggplot()`, `lm()`

If the function takes (and you supply) a data argument, then you do **not** need to use `data$variable`.